DIAGNOSTIC TABLE

Models:

AEI1G30LT - GR9FI30LTR5IAA AEI1G30EMX - GR9FI30R5IBA AEI1G40LT - GR9FI40LTR5IAA AEI1G50LT - GR9FI50LTR5IAA

INDICATION ON OUTDOOR UNIT

★ LED ON

X LED OFF

★ LED BLINKING

RANK	DIAGNOSIS CONTENTS	DL3	DL4	DL5	DL6	DL7
10	-CDT PROBE DAMAGED OR NOT CONNECTED	X	-\(\frac{1}{2}\)	X	X	X
9	-OAT PROBE DAMAGED OR NOT CONNECTED	X	X	-)	X	X
8	-OCT PROBE DAMAGED OR NOT CONNECTED	X	X	X	- D	X
7	-COMPRESSOR OVERCURRENT	X	X	X	X	₩
6	-COMPRESSOR OVERTEMPERATURE	-)\(\frac{1}{2}\)	-)h	X	X	X
5	-FAN OVERCURRENT	X	-)h	- J	X	X
4	-FAN OVERTEMPERATURE	X	X	₩	- J	X
3	-FAULT ON INDOOR UNIT	X	X	X	- J	₩
2	-COMUNICATION ERROR	-)\(\frac{1}{2}\)	⊅	₩	X	X
1	-PFC PROTECTION	X	A	*	A	X

LEGENDA:

CDT = Compressor discharge temperature

OAT = Outdoor air temperature

OCT = Outdoor coil temperature

PFC = Power factor corrector

UNIT WORKING PROPERLY:

- all indoor units are switched off

- at least one indoor unit is switched on

DL3 = ON

DL3 = ON, DL4 = ON